

Biogas Combined Heat and Power Unit

ENERGIN® M06 CHP B200

Datasheet, 500 mg NO_x



The ENERGIN® CHP combined heat and power unit simultaneously generates electricity and uses the heat from the engine jacket water and exhaust to heat water. The power output can be controlled between 50 and 100 % of nominal rating. It can be operated in parallel with the public network or with an isolated load. As an option, automatic emergency operation and/or island-parallel operation with other generators is possible.

The unit is supplied as a compact, fully functional unit, with or without a sound attenuating enclosure. The engine, generator, heat exchangers for oil and jacket water and exhaust as well as the control and power panel are mounted, ready for operation on the vibration-decoupled base frame. A lubrication oil system, which allows operation of up to 2000 hours without manual lube oil refilling, is integrated on the unit.

The electrical control system provides protection and control functions for automatic or manual operation. A 12" touch panel informs about operating conditions and allows the operation and parameterization of the system. Various interfaces are available for communication with other power generators and an overhead control system. An Ethernet interface allows connection to the Internet for remote monitoring and remote maintenance.

The entire system is certified according to the BDEW medium voltage directive (Grid code).

TECHNICAL DATA

Manufacturer	R Schmitt Enertec	
ENERGIN® Type	M06 CHP B200	
Electrical power ¹	kW	200
Thermal power ²	kW	213
Gas consumption ³ (LHV)	kW	479
Self consumption ⁴	kW	2,3

DESIGN

Fuel type	Biogas (50% Methane)	
Lower heating value LHV	kWh/Nm ³	5,0
Gas flow pressure ⁵	kPa	2,2 - 5,0
Inlet air temperature	°C	20
Exhaust temperature	°C	180
Hot water temperature ⁶	°C	70 / 90
Hot water flow rate	m ³ /h	#NAME?

EXHAUST EMISSIONS⁷ WITHOUT CATALYST

NO _x ⁸	mg/Nm ³	500
CO	mg/Nm ³	1000
Formaldehyde	mg/Nm ³	100

ENGINE

Manufacturer	R Schmitt Enertec	
ENERGIN® Type	M06-BTID41	
Working principle	4-stroke	
Cylinder configuration	6 in V / 90°	
Valves per cylinder	4	
Aspiration	turbocharged	
Mixture cooling	internal	
Displacement	ltr	11,3

LUBE OIL

Lube oil volume	ltr	255
Consumption	ltr/OH	0,06

ALTERNATOR

Manufacturer	Leroy Somer	
Type	LSA 46.3 L11	
Voltage	V / Hz	400 / 50
Speed	1/min	1.500
Efficiency	%	95,8



PERFORMANCE⁹

Load		100 %	75 %	50 %
Electrical power	kW	200	150	100
Thermal power	kW	213	166	124
Fuel consumption	kW	479	367	263
Gas flow at LHV	Nm ³ /h	96	74	53
Electrical efficiency	%	41,8	40,9	38,0
Thermal efficiency	%	44,5	45,2	47,1
Total efficiency	%	86,3	86,1	85,1
Exhaust gas flow ¹⁰	m ³ /h	1.151	845	579
Air requirement	m ³ /h	5.132	4.219	3.523
Exhaust air ¹¹	m ³ /h	4.374	3.663	3.142

DIMENSIONS AND WEIGHTS WITH SOUND ENCLOSURE

Length	mm	3.240
Height	mm	2.030
Height with 90° elbow	mm	2.950
Width	mm	1.470
Dry weight	kg	3.810
Operational weight	kg	4.220

CONNECTIONS

Exhaust	DN / PN	150 / 10
Fuel gas	DN / PN	50 / 16
Exhaust air	mm	720 x 720
Process water	DN / PN	50 / 16
Exhaust condensate	DN / PN	Rp 1/2"

¹ +0 % tolerance on electrical power output

² - 3/+ 8 % tolerance for thermal power @ 180 °C

³ +5 % tolerance on fuel consumption

⁴ average self consumption without emergency cooling

⁵ maximum variation of 10 % for set value

⁶ Return/flow temperature

⁷ Exhaust emissions related to 5 % oxygen in dry exhaust

⁸ Setup for 250 mg/Nm³ NO_x possible (changed performance data)

⁹ at standard conditions according to ISO 3046-1; cos φ = 1

¹⁰ wet exhaust gas at 180 °C

¹¹ ΔT = 15 K



R Schmitt Enertec GmbH
Siemensstraße 13
56743 Mendig - Germany
Phone +49 2652 93518 10
Fax +49 2652 93518 22

R Schmitt Enertec International FZCO
Apricot Tower, Office # 804, PO Box 341299
Dubai Silicon Oasis, DSO, UAE
Phone +971 4 333 5724
Fax +971 4 333 9133

www.rschmitt-enertec.com
info@rschmitt-enertec.com